


SECTION A-A

NOTE:

- GRIP RANGE: .020 - .080
- HOLE SIZE: .266 +.006/-.000 AFTER ALL APPLIED FINISHES.
- INSTALLED LENGTH: .305 MAX.
- LUBRICATION: WAX
- INSTALLATION TOOL: SSG 801 SPIN SPIN

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.002		DRAWN	JVK 8/22/08
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994		CHECKED	
MATERIAL		ENG APPR.	JVK 8/22/08
5056 ALUMINUM		MFG APPR.	AA 8/22/08
FINISH		Q.A.	
NONE		COMMENTS:	
NEXT ASSY		E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358	
USED ON			
APPLICATION		DO NOT SCALE DRAWING	



TITLE: SMALL FLANGE OPEN END

SIZE	DWG. NO.	REV
A	CAK3-0832-080	A
SCALE: 2:1	WEIGHT: kg	SHEET 1 OF 1