



SECTION A-A

NOTE:

1. GRIP RANGE: .027 - .165
2. HOLE SIZE: .391 +.006/-.000 AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: 1.005 MAX.
4. INSTALLED THREAD DEPTH: .895 REF.
5. LUBRICATION: NONE
6. INSTALLATION TOOL: MS 50 SPIN PULL

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	NEW RELEASE	5/23/2005	TOO
	B	ECN 1053	10/18/2007	TOO

**PROPRIETARY AND CONFIDENTIAL**

THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.  
SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:	NAME	DATE
		DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±1 BEND ±1 TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.002	DRAWN	TOO 5/23/05
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED	
		MATERIAL	ENG APPR.	TOO 5/23/05
		302/303 STAINLESS	MFG APPR.	AJP 5/23/05
		FINISH	Q.A.	
		PASSIVATE	COMMENTS:	
NEXT ASSY	USED ON		E-mail: info@sherex.com	
			www.sherex.com	
			Phone: 866-474-3739	
			Fax: 716-875-0358	
		APPLICATION		
		DO NOT SCALE DRAWING		



TITLE:  
LARGE FLANGE CLOSED END

SIZE	DWG. NO.	REV
<b>A</b>	CAL1-2528-165B	<b>B</b>
SCALE: 2:1	WEIGHT: .0115 kg	SHEET 1 OF 1