



SECTION A-A

NOTE:

1. GRIP RANGE: .020 - .080
2. HOLE SIZE: .266 +.006/- .000 AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: .305 MAX.
4. LUBRICATION: WAX
5. INSTALLATION TOOL: SSG 801 SPIN SPIN

**PROPRIETARY AND CONFIDENTIAL**  
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.  
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
		DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .002		DRAWN	TOO	
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994		CHECKED		TITLE: LARGE FLANGE OPEN END
		MATERIAL		ENG APPR.	TOO	
		A5056		MFG APPR.	AJP	5/23/05
		FINISH		Q.A.		SIZE DWG. NO. <b>A</b> CAL3-0632-080 REV A
NEXT ASSY		USED ON		COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		
APPLICATION		DO NOT SCALE DRAWING				
				SCALE: 2:1	WEIGHT: kg	SHEET 1 OF 1