



SECTION A-A

NOTE:

1. GRIP RANGE: 0.75 - 2.95
2. HOLE SIZE: 11.89 +.15/-.00 A/F AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: 13.08 REF.
4. INSTALLED THREAD DEPTH:
5. LUBRICATION: NONE
6. INSTALLATION TOOL: MS 100 SPIN PULL

REVISIONS			
REV.	DESCRIPTION	DATE	ECN
A	INITIAL RELEASE	6/21/10	1324
B	NEW FINISH PER SFS-01-001, SC2	2/26/15	1784

**PROPRIETARY AND CONFIDENTIAL**  
THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.  
  
SHEREX RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS TOLERANCES:  ANGULAR: MACH ±1 BEND ±1 TWO PLACE DECIMAL ±.10 THREE PLACE DECIMAL ±.05  INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	NAME	DATE
			CL	6/21/10
			JVK	6/21/10
			JVK	6/21/10
		MATERIAL C1008/C1010	COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358	
NEXT ASSY	USED ON	FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2		
APPLICATION		DO NOT SCALE DRAWING		



TITLE:  
**FLAT HEAD FULL HEX**

SIZE <b>A</b>	DWG. NO. CFH2-1015-2.9	REV B
------------------	---------------------------	----------

SCALE: 2:1 WEIGHT: kg SHEET 1 OF 1