

SECTION A-A


NOTE:

1. GRIP RANGE: 0.50 - 2.15
2. HOLE SIZE: 6.35 +0.15/-0.00 A/F AFTER ALL APPLIED FINISHES.
3. INSTALLED LENGTH: 6.72 REF
4. INSTALLED THREAD DEPTH:
5. LUBRICATION: NONE
6. INSTALLATION TOOL: SPIN-PULL

REVISIONS			
REV.	DESCRIPTION	DATE	ECN
A	INITIAL RELEASE	6/23/10	1324
B	NEW FINISH PER SFS-01-001, SC2	2/26/15	1784

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING, AND THE INFORMATION CONTAINED HERIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENT TO THE INTEREST OF THE COMPANY.
 SHEREX RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS TOLERANCES:	NAME	DATE
		ANGULAR: MACH ±1 BEND ±1 TWO PLACE DECIMAL ±.10 THREE PLACE DECIMAL ±.05	DRAWN	CL 6/23/10
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994	CHECKED	
		MATERIAL C1008/C1010	ENG APPR.	JVK 6/23/10
		FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2	MFG APPR.	
NEXT ASSY	USED ON		Q.A.	JVK 6/23/10
APPLICATION		DO NOT SCALE DRAWING	COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358	



TITLE:
FLAT HEAD FULL HEX

SIZE A	DWG. NO. CFH2-580-2.1	REV B
SCALE: 3:1	WEIGHT:	SHEET 1 OF 1