


- NOTE:**
- GRIP RANGE: 7.1 - 12.7
 - HOLE SIZE: 12.70 +0.15/-0.0 AFTER ALL APPLIED FINISHES.
 - INSTALLED LENGTH: 14.48 REF.
 - LUBRICATION: WAX
 - INSTALLATION TOOL: SSG 803 SPIN SPIN

REVISIONS			
REV.	DESCRIPTION	DATE	ECN
B	CORRECTION TO BULBED DIAMETER SPEC.	7/10/08	1086
C	NEW FINISH PER SFS-01-001, SC2	1/26/15	1751

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING, AND THE INFORMATION CONTAINED HEREIN, ARE THE PROPERTY OF SHEREX AND ARE NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTEREST OF THE COMPANY.
 SHEREX SOLUTIONS RESERVES THE RIGHT TO REVISE PART/DRAWING WITHOUT NOTICE.

		UNLESS OTHERWISE SPECIFIED:
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: ANGULAR: MACH ± 1 BEND ± 1 ONE PLACE DECIMAL ± 0.10 TWO PLACE DECIMAL ± 0.05
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994
		MATERIAL C1008/C1010
		FINISH ZINC PLATE W/YELLOW TRIVALENT CHROMATE PER SFS-01-001, SC2
NEXT ASSY	USED ON	
APPLICATION		DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	TOO	5/23/05
CHECKED		
ENG APPR.	TOO	5/23/05
MFG APPR.	AJP	5/23/05
Q.A.		
COMMENTS: E-mail: info@sherex.com www.sherex.com Phone: 866-474-3739 Fax: 716-875-0358		

		
SIZE	DWG. NO.	REV
A	CPB2-8125-12.7	C
SCALE: 2:1	WEIGHT: .0174 kg	SHEET 1 OF 1